



SAFETY DATA SHEET
Pirtek Hydraulic Oil 15

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name Pirtek Hydraulic Oil 15
Product number P8020
Internal identification GHS22743

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Hydraulic oil.
Uses advised against Non specified unless otherwise stated within this MSDS

1.3. Details of the supplier of the safety data sheet

Supplier Pirtek UK Ltd
 199 The Vale
 Acton
 London
 W3 7QS
 Tel: 0208 749 8444
 Fax: 0208 749 8333
 info@pirtek.co.uk

1.4. Emergency telephone number

Emergency telephone Pirtek UK Ltd Emergency Tel: 0800 382 438
 Mon – Fri 9am – 5pm

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification

Physical hazards Not Classified
Health hazards Asp. Tox. 1 - H304
Environmental hazards Not Classified

Classification (67/548/EEC or -
 1999/45/EC)

2.2. Label elements

Pictogram



Signal word Danger

Pirtek Hydraulic Oil 15

| | |
|---------------------------------|--|
| Hazard statements | H304 May be fatal if swallowed and enters airways. |
| Precautionary statements | P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor. P331 Do NOT induce vomiting. P405 Store locked up. P501a Dispose of contents/container to hazardous or special waste collection point. |
| Contains | Distillates (petroleum), solvent-dewaxed heavy paraffinic, Hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics |

2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

| | |
|--|--|
| Distillates (petroleum), solvent-dewaxed heavy paraffinic | 60-100% |
| CAS number: 64742-65-0 | EC number: 265-169-7 |
| | REACH registration number: 01-2119471299-27-XXXX |
| Classification | Classification (67/548/EEC or 1999/45/EC) |
| Asp. Tox. 1 - H304 | - |
| Hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics | 10-30% |
| CAS number: — | EC number: 934-956-3 |
| | REACH registration number: 01-2119827000-58-XXXX |
| Classification | |
| Asp. Tox. 1 - H304 | |

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

| | |
|----------------------------|---|
| General information | Get medical attention if any discomfort continues. |
| Inhalation | If spray/mist has been inhaled, proceed as follows. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Get medical attention immediately. |
| Ingestion | Get medical attention if any discomfort continues. Do not induce vomiting. Product contains petroleum based material, which, if aspirated into the lungs may result in chemical pneumonia. |
| Skin contact | Remove contaminated clothing immediately and wash skin with soap and water. |
| Eye contact | Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Get medical attention promptly if symptoms occur after washing. |

4.2. Most important symptoms and effects, both acute and delayed

| | |
|----------------------------|---|
| General information | If aspiration into the lungs is suspected, eg when vomiting, admit to hospital immediately. |
| Inhalation | Upper respiratory irritation. Harmful by inhalation. |

Pirtek Hydraulic Oil 15

| | |
|---------------------|--|
| Ingestion | May cause discomfort if swallowed. The product contains mineral oil, which if aspirated into the lungs through vomiting after ingestion, may result in chemical pneumonia. |
| Skin contact | Prolonged contact may cause redness, irritation and dry skin. |
| Eye contact | Irritation of eyes and mucous membranes. |

4.3. Indication of any immediate medical attention and special treatment needed

| | |
|-----------------------------|------------------------|
| Notes for the doctor | Treat symptomatically. |
|-----------------------------|------------------------|

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Extinguish with foam, carbon dioxide, dry powder or water fog.

Unsuitable extinguishing media Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards Heat from fire could result in drums bursting

Hazardous combustion products Protection against nuisance dust must be used when the airborne concentration exceeds 10 mg/m³. Oxides of carbon. Oxides of nitrogen. Fire may also create other unidentified organic gases some of which may be toxic.

5.3. Advice for firefighters

Protective actions during firefighting Control run-off water by containing and keeping it out of sewers and watercourses.

Special protective equipment for firefighters Wear self-contained breathing apparatus.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions For personal protection, see Section 8. In case of spills, beware of slippery floors and surfaces.

6.2. Environmental precautions

Environmental precautions Contain spillage with sand or earth. Avoid the spillage or runoff entering drains, sewers or watercourses. The product is insoluble in water and will spread on the water surface.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Contain spillage with sand or earth. Collect spillage for reclamation or disposal in sealed containers via a licensed waste contractor. Avoid water contacting spilled material or leaking containers. Spillages or uncontrolled discharges into watercourses must be reported immediately to the Environmental Agency or other appropriate regulatory body. In case of spillage on water prevent the spread by use of suitable barrier equipment

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8. See Section 11 for additional information on health hazards. For waste disposal, see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Pirtek Hydraulic Oil 15

Usage precautions Avoid spilling. Always remove oil with soap and water or skin cleaning agent, never use organic solvents. Do not use oil-contaminated clothing or shoes, and do not put rags moistened with oil into pockets.

Advice on general occupational hygiene Do not eat, drink or smoke when using this product.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store in tightly-closed, original container in a dry, cool and well-ventilated place.

Storage class Miscellaneous hazardous material storage.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

Distillates (petroleum), solvent-dewaxed heavy paraffinic

Long-term exposure limit (8-hour TWA): ACGIH 5 mg/m³

Short-term exposure limit (15-minute): ACGIH 10 mg/m³

Highly refined mineral oil (C15 - C50)

Long-term exposure limit (8-hour TWA): 5 mg/m³

ACGIH = American Conference of Governmental Industrial Hygienists.

Distillates (petroleum), solvent-dewaxed heavy paraffinic (CAS: 64742-65-0)

DNEL - Inhalation; : 5.4 mg/m³

PNEC - ; 9.33 mg/kg

2-ethylhexyl zinc dithiophosphate (CAS: 4259-15-8)

DNEL Workers - Dermal; systemic effects: 0.14 mg/kg/day
 Workers - Inhalation; systemic effects: 0.422 ppm
 Workers - Inhalation; Long term systemic effects: 0.07 ppm
 Workers - Dermal; local effects: 0.09 mg/cm²
 Workers - Inhalation; local effects: 0.42 ppm
 Workers - Inhalation; Long term systemic effects: 0.21 ppm
 Workers - Dermal; Long term systemic effects: 0.09 mg/cm²
 Workers - Dermal; Long term systemic effects:

PNEC - Fresh water; 0.004 mg/l
 - Soil; 0.0548 mg/kg
 - Sediment (Freshwater); 0.0701 mg/kg
 - Marine water; 0.0046 mg/l
 - Sediment (Marinewater); 0.00701 mg/kg
 - STP; 3.8 mg/l
 - Air; 7.1 mg/m³

benzenesulfonic acid, mono-C16-24-alkyl derivs.

Pirtek Hydraulic Oil 15

| | |
|-------------|---|
| DNEL | Workers - Dermal; Long term systemic effects: 3.33 mg/kg Workers - Inhalation; Long term systemic effects: 0.66 mg/m ³ Consumer - Dermal; Long term systemic effects: Consumer - Inhalation; Long term systemic effects: 0.33 mg/m ³ Consumer - Oral; Long term systemic effects: |
| PNEC | - Fresh water; 1 mg/l - Soil; 868700000 mg/kg - Sediment (Freshwater); 723500000 mg/kg - STP; 100 mg/l - Marine water; 1 mg/l - Intermittent release; 10 mg/l - Sediment (Marinewater); 723500000 mg/kg |

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate general and local exhaust ventilation. Observe any occupational exposure limits for the product or ingredients.

Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. The following protection should be worn: Chemical splash goggles or face shield.

Hand protection

The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material.

Other skin and body protection

Use barrier creams to prevent skin contact.

Hygiene measures

Use engineering controls to reduce air contamination to permissible exposure level. Wash promptly with soap and water if skin becomes contaminated.

Respiratory protection

Respiratory protection must be used if the airborne contamination exceeds the recommended occupational exposure limit.

Thermal hazards

Not anticipated under normal conditions of use. The product is combustible if heated excessively and an ignition source is applied.

Environmental exposure controls

Do not allow product to contaminate land.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

| | |
|------------------------|---------------------------|
| Appearance | Liquid. |
| Colour | Pale yellow |
| Odour | Characteristic. Oil-like. |
| Odour threshold | Not determined. |
| pH | Not applicable. |
| Melting point | -37°C |

Pirtek Hydraulic Oil 15

| | |
|---|---|
| Initial boiling point and range | >320°C @ 101.3 kPa |
| Flash point | 160°C |
| Upper/lower flammability or explosive limits | Not known. |
| Other flammability | Product is not flammable but on excessive heating may become combustible. |
| Vapour pressure | <0.1 kPa @ 20°C |
| Vapour density | Not determined. |
| Relative density | 0.860 @ 15°C |
| Solubility(ies) | Insoluble in water. Soluble in the following materials: Organic solvents. |
| Partition coefficient | Not determined. |
| Auto-ignition temperature | Not determined. |
| Decomposition Temperature | Not determined. |
| Viscosity | 15 cSt @ 40°C |
| Explosive properties | Not considered to be explosive. |
| Explosive under the influence of a flame | Not considered to be explosive. |
| Oxidising properties | The mixture itself has not been tested but none of the ingredient substances meet the criteria for classification as oxidising. |

9.2. Other information

| | |
|----------------------------------|--|
| Volatile organic compound | The product is a complex mixture, the majority of which would not be classed as a VOC. However it cannot be discounted that trace or low levels of VOC's may be present. |
|----------------------------------|--|

SECTION 10: Stability and reactivity

10.1. Reactivity

| | |
|-------------------|---|
| Reactivity | There are no known reactivity hazards associated with this product. |
|-------------------|---|

10.2. Chemical stability

| | |
|------------------|---|
| Stability | Stable at normal ambient temperatures and when used as recommended. |
|------------------|---|

10.3. Possibility of hazardous reactions

| | |
|---|--|
| Possibility of hazardous reactions | Unlikely to occur under normal conditions of use. Unlikely to occur. |
|---|--|

10.4. Conditions to avoid

| | |
|----------------------------|---|
| Conditions to avoid | Avoid heat, flames and other sources of ignition. |
|----------------------------|---|

10.5. Incompatible materials

| | |
|---------------------------|--------------------------|
| Materials to avoid | Strong oxidising agents. |
|---------------------------|--------------------------|

10.6. Hazardous decomposition products

| | |
|---|---|
| Hazardous decomposition products | Oxides of carbon. Toxic gases/vapours/fumes of: Carbon monoxide (CO). |
|---|---|

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Pirtek Hydraulic Oil 15

Acute toxicity - oral

Notes (oral LD₅₀) Not expected to be highly toxic based on information of ingredients.

Acute toxicity - dermal

Notes (dermal LD₅₀) Not expected to be highly toxic based on information of ingredients.

Acute toxicity - inhalation

Notes (inhalation LC₅₀) Not determined. The product is unlikely to present any significant inhalation hazard at ambient temperatures and under normal conditions of use.

Serious eye damage/irritation

Serious eye damage/irritation May cause mild, short lasting discomfort to eyes.

Respiratory sensitisation

Respiratory sensitisation Repeated exposure to oil mists may cause respiratory damage.

Skin sensitisation

Skin sensitisation Not expected to be a skin sensitizer based on information on components.

Reproductive toxicity

Reproductive toxicity - fertility No data available to suggest the product will cause reproductive toxicity.

Aspiration hazard

Aspiration hazard Kinematic viscosity ≤ 20.5 cSt @ 40 C. Product may be considered an aspiration hazard under CLP regulations.

General information

This product has low toxicity. Only large quantities are likely to have adverse effects on human health.

Inhalation

Unlikely to be hazardous by inhalation because of the low vapour pressure of the product at ambient temperature. High concentrations of vapours may irritate respiratory system and lead to headache, fatigue, nausea and vomiting.

Ingestion

Swallowing significant quantities may cause discomfort, nausea, diarrhoea and irritation of the digestive tract. Aspiration into the lungs (e.g. through vomiting) after ingestion can be hazardous with possible resultant chemically induced pneumonia.

Skin contact

Skin irritation should not occur when used as recommended. Repeated exposure may cause skin dryness or cracking.

Eye contact

May cause temporary eye irritation.

Acute and chronic health hazards

Prolonged or repeated contact with used oil may cause serious skin diseases, such as dermatitis and skin cancer.

SECTION 12: Ecological Information

Ecotoxicity

The product is not expected to be hazardous to the environment.

12.1. Toxicity

12.2. Persistence and degradability

Persistence and degradability

The product is not classed as being readily biodegradable by OECD test methods but is considered inherently biodegradable.

Stability (hydrolysis)

The product is based on highly refined mineral oils that are considered stable to hydrolysis.

Biodegradation

The product is not considered readily biodegradable, albeit the major constituents are expected to ultimately biodegrade.

Pirtek Hydraulic Oil 15

Biological oxygen demand Not determined.

Chemical oxygen demand Not determined.

12.3. Bioaccumulative potential

Bioaccumulative potential Bioaccumulation is unlikely to be significant because of the low water-solubility of this product.

Partition coefficient Not determined.

12.4. Mobility in soil

Mobility The product is non-volatile. The product is insoluble in water and will spread on the water surface.

Henry's law constant Not determined.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

Other adverse effects None known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Waste should be treated as controlled waste. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

Disposal methods Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

SECTION 14: Transport information

General The product is not covered by international regulations on the transport of dangerous goods (IMDG, IATA, ADR/RID).

14.1. UN number

Not applicable.

14.2. UN proper shipping name

Not applicable.

14.3. Transport hazard class(es)

No transport warning sign required.

14.4. Packing group

Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

14.6. Special precautions for user

Not applicable.

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Pirtek Hydraulic Oil 15

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

| | |
|-----------------------------|--|
| National regulations | Health and Safety at Work etc. Act 1974 (as amended). The Pollution Prevention and Control Act 1999. Special Waste regulations 1996. Control of Pollution (Oil Storage) (England) Regulations 2001 The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (SI 2009 No. 716). |
| EU legislation | Dangerous Preparations Directive 1999/45/EC. Dangerous Substances Directive 67/548/EEC. Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended). Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended). |
| Guidance | Workplace Exposure Limits EH40. Safety Data Sheets for Substances and Preparations. |

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

Inventories

EU - EINECS/ELINCS

All the ingredients are listed or exempt.

Canada - DSL/NDSL

All the ingredients are listed or exempt.

US - TSCA

All the ingredients are listed or exempt.

Korea - KECI

All the ingredients are listed or exempt.

China - IECSC

All the ingredients are listed or exempt.

Philippines – PICCS

All the ingredients are listed or exempt.

New Zealand - NZIOC

All the ingredients are listed or exempt.

SECTION 16: Other information

| | |
|--------------------------|--|
| Revision comments | NOTE: Lines within the margin indicate significant changes from the previous revision. |
| Issued by | Regulatory Affairs |
| Revision date | 29/03/2016 |

Pirtek Hydraulic Oil 15

| | |
|----------------------------------|--|
| Revision | 1 |
| SDS number | 22743 |
| Risk phrases in full | Not classified. |
| Hazard statements in full | H304 May be fatal if swallowed and enters airways. |

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.